

# Sure Primer FC

Fairing Coat Repair Primer



**Tilt-Lift Equipment Pty Ltd**  
ABN 76 005 928 987  
CONCRETE ACCESSORIES

## PRODUCT DESCRIPTION:

Tilt Lift Equipment Sure Primer FC is a general acrylic bonding bridge and a primer for Sure Mortar FC.

## PURPOSE:

Sure Primer FC is specifically formulated to prepare the surface of architectural panels to be repaired with Sure Mortar FC.

## ADVANTAGES:

- Water Based
- Shipped in ready to use containers
- Easy application
- Excellent adhesion

## APPLICATION INSTRUCTIONS:

### Surface preparation:

The concrete must be sound and free of all foreign material, including oil, grease and any other surface contaminants. All concrete must be mechanically scarified, shot blasted or similarly treated to obtain a profiled or roughened surface. To reduce substrate porosity, dampen the concrete surface with water to create a saturated surface dry condition before priming.

### Applying:

Evenly apply Sure Primer FC with a brush or spray. While primer is still tacky, place Sure Mortar FC.

DO NOT attempt to dilute Sure Primer FC.

DO NOT use at temperatures below 5°C or above 35°C.

### Curing:

Sure Primer FC is suitable as a low efficiency curing compound in some cases. Contact Tilt-Lift Equipment's technical department for advice.

## CLEAN UP:

Immediately clean all equipment with water after use.

## PACKAGING:

Sure Primer FC is packaged in 1, 4 and 20 litre containers.

## LIMITATIONS:

DO NOT attempt to dilute Sure Primer FC. Not suitable where repairs are permanently immersed in water.

## APPROXIMATE COVERAGE RATES:

Prime Coat ..... 5m<sup>2</sup>/L  
Cure Coat ..... 5m<sup>2</sup>/L

Texture and absorption of substrate will dictate prime coat coverage rate.

## TEST DATA:

Bond Strength @ 20°C ..... >1.5MPa

## STORAGE:

Store in the original unopened containers. DO NOT allow product to freeze.

## WARNING:

In case of contact with eyes, immediately flush with water for at least 15 minutes.

Avoid hazards by following all precautions found in the Material Safety Data Sheet, product labels and technical literature. Please read this information prior to using the product.

## TECHNICAL SERVICES:

Call the technical staff for assistance at:

03 9583 0115

or

Fax: 03 9583 9293

Visit the website at:

[www.tiltlift.com.au](http://www.tiltlift.com.au)

Also, Tilt-Lift Equipment's coast to coast network of distributors and dealers are well informed on capability and applications procedures.